

SKID STEER HYDRAULIC BREAKER



FEATURES:

Accumulator-free hybrid design combines gas and hydraulic power with fewer moving parts | Long-stroke piston and cushion chamber technology maximize impact while reducing recoil | Dual retainer pin design maintains proper tool alignment for even wear

- ➔ Available in Bobcat and Kubota quick-coupler configurations
- ➔ Ideal for demolition, concrete breaking, rock excavation, trenching, road repair, and utility installation
- ➔ Heavy-duty construction is engineered for demanding construction, utility, municipal, and rental fleet environments.

SPECIFICATIONS

SKUs	Impact Energy Class	Impact	Working Weight — 1pc top mount	Working Weight — 2pc top mount	Working Weight — box bracket
212-SSMX-BC (fits Bobcat) & 212-SSMX-KUB (fits Kubota)	825 ft-lb (1,118 Nm)	550– 1,000 bpm	672 lbs (305 kg)	694 lbs (315 kg)	849 lbs (385 kg)
Operating Pressure	Oil Flow	Chisel Diameter	Hose Size	Base Carrier Class	N2 Gas Charge Pressure
1,450–2,320 PSI (10–16 MPa)	9.2–15.3 GPM (35–60 L/min)	3.0" (75 mm)	1/2"	3.8–6 metric tons	8 bar (116 psi)



4101 Garland Drive Fort Worth TX 76117
Phone | 817-485-6073 Fax | 817-428-6008
USA & Canada Toll Free 800-541-1797

www.starindustries.com

Operating Manual and Safety
Information available online.